

seaco

T11-T14 INSULATED & UNINSULATED TANKS

DESIGNED FOR HAZARDOUS, NON-HAZARDOUS AND FOOD GRADE CARGOES

— AVAILABLE IN A WIDE RANGE OF CAPACITIES WITH OR WITHOUT BAFFLES



**RIGHT CONTAINER,
RIGHT PLACE, RIGHT TIME**

FEATURES

- TOP DISCHARGE FLANGE
- 8 STEAM HEATING RUNS
- PRV WITH VACUUM RELIEF VALVE
- 45° UNIVALVE BOTTOM OUTLET VALVE
- FITTED WITH "B" TYPE WALKWAY AND OPTION TO FIT HANDRAILS
- NON SLIP STAINLESS STEEL LADDER
- STAINLESS STEEL BARREL
- BAFFLES (OPTIONAL)

ADVANTAGES

- ADAPTABLE DESIGN
- REDUCED STEAMING TIME
- PROTECTS THE TANK FROM EXCESSIVE OVER PRESSURE OR VACUUM
- EASIER UNLOADING
- IMPROVED ACCESS AND ADDED SAFETY
- FOR EASY AND SAFE ACCESS TO TOP FITTINGS AND TOP CORNER CASTINGS
- RESISTANCE TO CHEMICAL ATTACK
- FOR LIQUID SURGE/ LOADSHIFT REDUCTION

BENEFITS

- OPTIONAL FILL/ DISCHARGE COMBINATIONS
- LOWER OPERATING COSTS
- SAFETY AND REDUCED RISK OF VACUUM IMPLOSION
- IMPROVED SAFETY AND EFFICIENCY
- ACCORDS WITH ITCO H&S DIRECTIVE
- ACCORDS WITH ITCO H&S DIRECTIVE
- COMPATIBLE WITH A WIDE VARIETY OF CARGOES
- IMPROVED SAFETY



ANTWERP • BRISBANE • CAPE TOWN • DURBAN • GOTHENBURG • HAMBURG • HOUSTON • LISBON • LONDON • MADRID
 MIAMI • MOSCOW • MUMBAI • PARIS • PERTH • RIODEJANEIRO • SEOUL • SHANGHAI • SINGAPORE • SYDNEY • TAIPEI • TOKYO

A MODERN FLEET OF 45,000 TANKS: BAFFLE TANKS, T11-T14 TANKS, SWAP TANKS, T20/T22 SPECIALISED TANKS, T50 GAS TANKS

TANKS IN ACCORDANCE WITH: UN PORTABLE TANK 11/ADR TANK L4BN, US-DOT, CFR49, UK-DFT, IMDG, ADR/RID, TC, FRA, AAR600, ISO 1496/3, CSC, TIR, UIC

Models available:

- ✓ T11-T14 tanks covering a full range of capacities up to 26kl
- ✓ Insulated and non-insulated versions – inner shell linings (ChemLine, Saekaphen, Butyl Rubber, Isoemail) available upon request
- ✓ 26kl baffle tanks with vertical and horizontal configurations
- ✓ Custom features available through Seaco tank engineering

	Metric	Imperial
Capacity	Up to 26,000 ltr	Up to 6,870 US Gallons
Maximum Gross Weight	36,000 kg	79,365 lb
Tare Weight	Up to 3,830 kg	Up to 8,443 lb
Length	6,058 mm	20 ft 0 in
Width	2,438 mm	8 ft 0 in
Height	2,591 mm	8 ft 6 in
Maximum Allowable Working Pressure (MAWP)	4.0 bar	58 psi
Test Pressure	6.0 bar	87 psi
Steam Working Pressure	4.0 bar	58 psi
Relief Valve Set Pressure	4.4 bar	63 psi
Ambient Temperature Range	-40°C to +65°C	-40°F to +149°F
Maximum Cargo Temperature	+130°C	+266°F
Shell and Head Material	SANS 50028-7 (2005):1.4402	

SEACO HAS A DEDICATED TEAM OF WORLDWIDE SPECIALISTS WHO HAVE CONSTRUCTED ONE OF THE LARGEST LEASING FLEETS OF SPECIALISED CONTAINERS. WITH OUR VAST EXPERIENCE IN THE INDUSTRY, WE WILL FIND THE RIGHT PRODUCT FOR YOUR NEEDS AND TAILOR OUR LEASE AGREEMENTS TO YOUR SPECIFIC REQUIREMENTS.

FOR DETAILED SPECIFICATIONS OF OUR PRODUCT OFFERING, PLEASE CONTACT YOUR REGIONAL SEACO TANK EXPERT.

AMERICAS

John Lonergan

(+1) 305 597 2129

john.lonergan@seacoglobal.com

EMEIA

Nils Meyer

(+49) 40 8080 3114

nils.meyer@seacoglobal.com

AFRICA: seacoglobal.co.za

NORTH ASIA

Koji Hattori

(+81) 3 4530 9802

koji.hattori@seacoglobal.com

S.EAST ASIA

John Ong

(+65) 6595 1916

john.ong@seacoglobal.com

OCEANIA

Ben Lowry

(+61) 7 3332 8514

ben.lowry@seacoglobal.com

seacoglobal.com.au



an HNA company